

## WMD-06 motorized swing gate with swing panels AGG-650 for indoor application



 <b>24 V</b>	 <b>105 W</b>	 <b>2</b>	 <b>12</b>
operating voltage	power consumption	passage directions	persons/min
 <b>+50</b> <b>+1</b>	 <b>IP41</b>		
temperature range	protection rating	motor drive	



The WMD-06 motorized swing gate with glass panel for indoor use is an up-market model that offers an elegant solution for entrance points of banks, administrative buildings, business centers and other sites with the highest requirements for design and comfort.

The WMD-06 features a tempered glass swing panel available in two versions: a standard panel (650 mm) or an extended panel (900 mm) for convenient wheel-chair access. In emergency situations the gate with the extended swing panel can be used as an additional emergency exit.

Operating voltage	24 V DC
Power consumption	105 W
Consumption current	4.4 A
Number of passage directions	2
Throughput rate (in the single passage mode)	12 persons/min
Dimensions (length×width×height)	795×147×1012 mm
Passageway width	700 mm
Operating temperature range	from +1 °C to +50 °C
IP Code	IP41

Gate post – stainless steel.



stainless steel

Swing panel – 10 mm tempered glass.

The warranty period is 5 (five) years from the date of sale of the product.





# REVROY

Solutions For Controlled Access

## CONTACT

Ravi@revroy.com | Info@revroy.Com

+91 080 41302021, +91 080 41571225, +91 9840294082

### SALES OFFICE

No.#13, Hamdh Court Building,  
Mother Teresa Road, Austin Town,  
Bangalore-560 047, India

### FACTORY

Plot No 143-B, Bommasandra Industrial Area  
Bangalore-560099, Karnataka. India.  
+91 80 41658921

“Finest from the very best from around the world”



[www.revroy.com](http://www.revroy.com)