



Technical Specifications

- Gross weight: 45KG
- Power Supply: AC85v - 264 v
- Working temperature: -20°C--+50°C
- Working Frequency :4KHZ—8KHZ
- Standard External size: 2230mm(H)X860mm(W)X480mm(D)
- Standard Internal size: 1990mm(H)X700mm(W)X400mm(D)
- Package size for door panels: 2290*560*190mm *1ctn
- Package size for control unit: 760*350*260 mm*1ctn

Areas of Applications



Port



Airport



Train Station



Hospital



Hotel



Factory



Government



Bank



Usage condition

RR-UB-400

Pinpoint Zone Detection

The Uniqscan' s exclusive multiple target pinpointing with 4 zones standard shows precise target location.

Program

When the program is self-diagnostic, it does not require initial or periodic calibration, modularization design, easy for maintenance and replacement.

Installation

RR-UB-400 design only 2 cables and 8 screws, operation instructions are simple. High density refractories are used to make the product stronger.



PRODUCT DETAILS



The RR-UB-400 Access Control Panel is designed for use by authorized personnel with specific, multi-level security with password protection, only the authorized person can operate ; Panel display function digital display, counting the number of passing and the number of alarms.

PRODUCT PACKAGING



Carton Dimension L*W*H (mm)
Door Panel : 2260*550*235 mm
Control Unit : 750*340*240 mm
Gross weight : 45KG

